

# XIM SPECIFICATION NO. 1011

DATE: April 26, 2005

UPDATED: April 26, 2005

## PRIMING STUCCO

### APPLICABLE SURFACES:

Poured, cast or blown as Latex Rich Plaster with Concrete. Used extensively with metal lath. Primarily used exterior. Used as a fine plaster for decorative work moldings.

### BACKGROUND:

As an exterior finish, it finds many uses. The material itself is a mixture of Portland cement, Lime and Sand.

### PRODUCTS:

#### Primers:

Advanced Technology UMA brand® White Water Based Bonding Primer (Product No. 1105)

Advanced Technology UMA brand® Tintable Water Based Bonding Primer (Product No. 1106)

Peel Bond Water Based. Clear Bonder / Sealer (Product No. 1146)

X-Out Latex White Stain Killer (Product No. 1125)

X-Out Plus Latex White, Stain Killer (Product No. 1127)

601 Clear Water Reduced Masonry Sealer (Product No. 1133)

### Top Coat Paints:

**INTERIOR / EXTERIOR Oil** Alkyds or Latex (Where compatible with primer), Epoxy and Urethane (Where compatible with the primer).

### SURFACE PREPARATION:

In general, the key requirement is "clean". Where forms are used, release compounds are used to save the form. These agents must be removed before any coatings are applied. Use a Solvent Base cleaner. If PH is an issue, do not use Alkyd Products.

### APPLICATION:

Application of primers can be with brush, roller or spray.

### CONSIDERATIONS:

Any and all considerations and good procedure applicable to concrete will apply to stucco.

\*\*Make sure that Stucco is fully cured and contains less than 10% moisture.

XIM Products, Inc. 1169 Bassett Road, Westlake, OH 44145  
(800) 262-8469 Fax (440) 871-3027 www.ximbonder.com